EA39-8 Ceiling Microphone with reinforcement Al

SKU: 0110039-8 EAN:



FEATUES

The Edis EA39-8 Ceiling Microphone with reinforcement Al One is enough and ideal for a stan-da rd classroom, a middle conference room or a small church. It's easy to install whether on the desk or on the wall. Debug-free design, plug and play. Digital microphone array, 8-meter distance voice pickup. A hands-free lecture and presentation solution. Adaptive blind beamformingtechnologyautomatic speaker alignment and speech reinforcementto prevent from interference and to keep speech clear. Multiple audio algorithms Using patenttechnologiesincluding Intelligentnoise reductionecho cancellation and reverberation suppression to ensure clear sound quality and comfortablecommunication. Requirements of the building of the classroom decoration are low. Supports full duplex. Simplified installation, plug and play. Using standard USB2.0 and 3.5 mm audio interfacedebug-free design, plug and play. Simple system and compact appearance, easy to install and maintain. Supports dual-mode (digital analog) output.



EA39-8

Directivity Characteristic	360°
Microphone Array	Built-in 7 microphone arrays to form a circular microphone array
Sensitivity	-26 dBFS
SNR	64dB(A)
Frequency Response	20Hz -16kHz
Sampling Rate	32K sampling, High Definition Broadband Audio
Pickup Radius	8m
USB Protocol	Support UAC
AEC	Support
ANS	Support
AGC	Support
Reverberation Suppression	Support

LNPUTJOUTPUT LNTERFACE

Audio Input	1 x 3.5mm Line In
Audio Output	2 x 3.5mm Line Out
USB Interface	Support UAC 1.0 protocol, audio data communications, software upgrade and parameter configuration
Power	USB DCSV
Dimensions	130mm x H 33mm