Mobile LCD Touchscreen Advertising stand with WiFi

SKU: 0030028



FEATUES

The Edis Mobile LCD Touchscreen Advertising stand with WiFilntegrated aluminum alloy frame, 1080 HD display multi-touch screen display, high quality sound, used in many locations to enhance advertising, wayfindingand information display requirements, to meet your needs. Cloud based servers, mobile phones, tablets, computers can all be used to manage media. Easy to use, builtin scheduling, folding non slip design, WiFi connection. Picture rotation, video playback, subtitles, silk screen logo printed on front, adjust the Angle of the display to suit, quality round cornered frame. A variety of split screen options, split screen area can be fine-tuned. Sensitive touchscreen control, U disk plug and play.





SPECIFICATION

Size	32inch	43inch	49inch	55inch	32inch	43inch	49inch	55inch
touch	no touch	no touch	no touch	no touch	capacitive	capacitive	capacitive	capacitive
					touch	touch	touch	touch
CPU	RK3288 2+8,	RK3288	RK3288					
	Android 7.1	2+8,	2+8,					

Android 7.1 Android 7.1

PANEL

Panel	32/43/55"
Resolution	1920×1080
Tresolution	1920^1000
Visual angle	H: 178° V: 178°
Brightness	350 cd/m2
Contrast	1400:1
Response time	6ms
Screen Life(hrs)	> 50,000(hrs)

OTHER PARAMETERS

Material	Toughened glass + aluminum		
_	profile frame		
Speaker	2×5W speakers (8Ω)		
Color	White Normally, OEM support		
Installation	Floor standing bracket		
Operating	0℃~50℃/20% ~ 80%		
temperature			
/humidity			
Store temperature/	-10℃~60℃/595%		
humidity			
Software support	Free installation applications		
	(maps, games, e-mail,		
	self developing apps, etc.)		

ATTACHMENT

Adapter	One

INTERFACE

USB USB 2.0

Warranty card	One
Qualification	One
certificate	
User's Manual	One
Screws and Wall	Support
mounted brackets	
Antenna	One

HDMI	Support
	One
LAN	One
DC IN	One
MIC IN	One
LIN OUT	One

CONFIGURATION CPU RK3288 Memory 2GB Storage 16GB OSD language Multi language support

Android 7.1 system

System

NETWOR	K	
Ethernet	100M/1000M	
WiFi	802.11 b/g/n (3G/4G)	
Bluetooth	Support BT v4.0	

MULTI-MEDIA	
Video	Support MPEG-1, MPEG-2, MPEG-4, H.263,
	H.264, RV, etc. (max support 1080P)
Audio	Support MP4, WMA, AAC and so on
Picture	JPEG, PNG, BMP and so on

POWER			
The input voltage	AC100-240v 50/60HZ		
Standby power	≤1W, support low power standby mode		