

FEATURES

- The Standard Podcast Kit for schools includes all items for indoor and outdoor activities but excluding the Studio Lighting Kit.
- The Standard Podcast Kit for schools includes all items for indoor and outdoor activities but excluding the Studio Lighting Kit
- This kit includes a 4k video camera and a Sports Activity camera with all accessories.
- An Audio Mixer with 99 DSP effects and a Sound card with pre-recorded pad keys to provide instant effects such as clapping and laughter etc, Wireless and wired microphones plus wireless and wired lapel (Lavalier) microphones, hand held recorder, headsets, and amplifier
- A ring light with stand for desk or floor and LED photo box is included
- Accessories such as mobile phone AI tracking Gimbal with all cables and adaptors to connect the equipment together, With this kit you can create professional podcasts for one person or a whole group indoors or outdoors to match your needs for enhanced learning activities
- The carry case is made from strongplastics material with foam mouldings tosecure items inside (and to ensure allitems retuned to their place) withwheels and handle for easy transportingand storage



SPECIFICATION

EC45 Mixer

Provide 8/12/16 inputs
8 mono, 2 stereo
The PAD attenuation is -20dB
3-band UK EQ:HIGH: Gain: +15 dB/-15dB, Frequency: 12kHz slope
MID: Gain: +15dB/-15dB, Frequency: 4kHz peak
LOW: Gain: +15dB/-15dB, Frequency: 80Hz slope
1*5 segments of LED level signal indicator per channel
2*12 Dot-Pitch LED Level Meter, LEVEL:[-36,-30,-24,-18,-12,-6,-3,0,+3,+6,+10,+20dB]
BUILT-IN DIGITAL EFFECTS, DSP ALGORITHMS, 99 KINDS OF PROGRAMMING, PARAMETER CONTROLLER
USB Audio, 2IN/2OUT USB2.0 compatible, dual-track recording
Phantom power:voltage +48V, each channel is independently controlled
Lossless USB music player, support decoding formats:WAV, WMA, APE, FLAC, MP3, support SD card, multi-track recording
Dual-channel headphone monitoring
2 sets of AUX SEND auxiliary outputs
Each independent REC multi-track recording control knob
1 set of TRTURN return function inputs
1 pin RCA stereo input
1 set of needle RCA stereo recording outputs
2GROUP OUT: group output
Dual-channel MAIN OUT stereo output
HIGHLY RELIABLE, SMOOTH 60MM TRAVEL FADERS

EC40 Smart Mixer Sound Card with condenser mic	Channel system: Double channel Battery :3.7V/1800mAh Shutdown current: 50u A Charging DC:5V/1A Headphone output: 320 10mW*2 Accompaniment input :600mv Microphone input: 42dB+3dB 1 X sound card 2 X Audio cable 1 X OTG USBC cable 1x condenser mic 1x desk stand 1 X Charging cable
Handheld Audio Recorder with X/Y Stereo Microphone	Handheld Audio Recorder with X/Y Stereo Microphone Recording format:WAV (44.1kHz/16bit, 44.1kHz/24bit, 48kHz/16bit,48kHz/24bit, 96kHz/16bit, 96kHz/24bit) Playback format:WAV (44.1kHz/16bit, 44.1kHz/24bit, 48kHz/16bit,48kHz/24bit, 96kHz/16bit, 96kHz/24bit) Analog-to-digital conversion:24-bit, 128x oversampled Digital-to-analog conversion:24-bit, 128x oversampled Signal processing:32-bit Screen:LCD LCD screen 128×64 (with backlight) Input:Built-in 90°XY stereo microphone:Maximum input sound pressure level 110dB SPL Sensitivity:-35dB Unidirectional heart LINE IN: 3.5mm TRS linear level input Gain 0 to 30dB Output:3.5mm stereo earphone monitoring hole:Max MIC to HP/OUT gain 48dB Line IN to HP/OUT with a maximum gain of 36dB Signal-to-noise ratio > 80dB (@60% volume, -30dBu input) THD+N distortion < 0.01% (@60% volume, -30dBu input) Frequency response 20Hz-20 KHZ (@LINE IN input) 20mW + 20mW into 32Ω load Built-in speaker:0.5W/ 8Ω USB output interface:Type-C Power supply:2 # 5 batteries (NIMH or alkaline) Type-C (DC 5V/1A) does not support charging Recording duration:16~20 hours (powered by Nanfu AA LR6 battery *2) SD card capacity:The maximum support is 128GB Packing :Lapel microphonex1 Type-C Data Cable (A to C) x1 lanyardx1 Windproof spongex1
Dynamic Microphone	Frequency Response Rate 40Hz ~ 12kHz Polar Pattern:Omni-directional Signal To Noise Ratio:70dB Maximum SPL:130dB Sensitivity:-39dB±2dB microphone Sensor Type:moving coil Pickup mode :heart-shaped Frequency response:40Hz-15KHz Sensitivity:-54.5dBV 6m leads
Wireless microphone with Bluetooth	Built-in lithium battery:1860 Battery life:about 8 hours Dimensions :303 * 192 * 60 mm Frequency band:UHF Signal to noise ratio:> 70dB Distortion:< 0.5% Operating frequency band:50 * 2 Frequency response:50-18 kHz Delay:> 3 ms Reception distance:30 m
4 Channel Headphone Amplifier	Output: 4x 3.5 mini jack , 4x 6.3 jack Input: 1x 3.5 mini jack, 1x 6.3 jack, 2x RCA Product Size:Approx. 14 x 9.6 x 3cm / 5.5 x 3.8 x 1.2in

	Package List 1 x Headphone Amplifier 1 x Plug 1 x USB Cable 1 x User Manual
5x EH13 Headphones 3.5/6.3 jack	musical instrument Headphones 3 meter cable / 6.5 jack or 3.5 mini jack in PE Bag/ no gift box
EH186 Wired headset	Speaker size:32mm Sensitivity:105±3dB Frequency range:20Hz-20KHz Microphone :6.0X2.7mm Microphone sensitivity:-38±3dB Directionality :omni-directional Headset jack &Cable length 1) Mini Jack:1.2M ±0.152) USB:3.3M ±0.15 Headset jack &Cable length 3) Mini Jack :1.2m +3.3M Usb Total:4.5M System support :Win 7/Win8/Win8.1/Win 10/XP
10 port UsB Charger	60W 10 Port UsB charger , Max output 5V 12A
Wired Lavalier microphone	Polar pattern:Omni-directional Frequency Range:20Hz ~ 20KHz Signal/ Noise:74dB SPL Sensitivity:-30dB +/- 3dB/ 0dB=1V/Pa, 1kHz Output Impedance:2200 Ohm or less Connector:3.5mm (1/8") 4-pole gold plug Accessories :Included lapel clip, LR626 battery, foam windscreen, 1/4" adapter Battery Type:LR626/1.5V Dimensions:Microphone: 15.00mmH X 8.00mmW X 8.00mmD Cable:6m*2 Weight:99.5g
Phone tablet tripod stand	Height:152cm Applicable Model :4.7inch-14.5inch Structure:360° Rotating Standard Accessorie: Tablet Holder*1 Clamp*1 Bag*1
LED Photo light box	Material:Polyester, EVA, polyester Weight:2320g
Smartphone AI Tracking Gimbal	Storage length:270mm Expand Length:700mm Pipe:Aluminum-alloytubing Function:AI face tracking gimbal Anti-shake:Intelligent anti-shake design Direction:One-touch horizontal and vertical shooting 270° 3D Inception Wireless remote control
Adjustable desktop microphone stand	Support expansion size:440mm Bracket telescopic height:440~710mm Inclined rod telescopic pipe:Φ15 Vertical rod lifting pipe:Φ15 Vertical pipe:Φ20 Floor area:140mm Support component:disc base Lift mode:lift lock knob Support weight:1.6KG